GHV	**3580**	**35120**	**35160**	**35200**	**35240**
CAPACITIES					
Swing over bed	900mm(35")				
Swing over carirage	750mm				
Distance between center	2000mm	3000mm	4000mm	5000mm	6000mm
HEADSTOCK					
Spindle bore	155mm (A2-11)/250mm(A2-15)/305mm380mm(A2-)20				
Spindle speed range	155mm 4-800rpm/250mm305mm380mm4-400rpm				
Spindle speed steps	4 steps				
Main motor	30HP with invertor				
Longitudinal feeds		0.04mm/rev	… 1.0mm/rev		
Longitudinal rapid	0.02mm/rev….0.5mm/rev				
CARRIAGE & APRON					
Width of carriage	900mm				
Width of cross slide	350mm				
Cross slide travel	390mm				
Compound slide travel	220mm				
Tool post	180mm				

Feed motor	3HP with invertor				
Tailstock					
Diameter of quill	165mm				
Travel of quill	250mm				
Center	M.T. #6				
Bed width	900mm(35.4")				
Net weight	5500kgs	6500kgs	7500kgs	8500kgs	9500kgs
Packing size W: 2200mm H: 2200mm	L:4700mm	L:5700mm	L:6700mm	L:7700mm	L:8700mm